

JETi 3300

Technology:

Print Resolution:

Media Dimensions:

Media Types:

RIPS:

Formats:

Inks:

Printing Speeds:

Weight:

Printer Dimensions:

Power Consumption:

Electrical Requirements:

Compressed Air:

Environment:

Relative humidity:

Warranty:

Price:

Spectra High Performance Piezoelectric Jetting Assembly, quantity 12.

300 dots per inch, unique 4/6 color combination. Prints high quality 600 dpi - 6 color (apparent); Or high speed 300 dpi - 4 color.

Roll substrate Max size: 3.2 meter/ 10'6" wide. Diameter 12"Max on a 3" ID core.

Reinforced Vinyl, Pressure Sensitive Vinyl, Canvas, Fabrics, Mesh and Paper.

Choice of Onyx PosterShop, Wasatch SoftRip, ColorGate, ErgoSoft on PC, And Caldera on the Mac.

EPS, Tiff, RGB, PostScript Level 3 etc..

1-3 years depending on location, Without a clear protective top coating. Using SWC top coat, print life will double.

> 6 Color 4 Color 600dpi 300dpi

Best Mode 340sf/hr 485sf/hr Production Mode 485sf/hr 655sf/hr User definable #passes vs % density

3500 lbs / 1590 kgs uncrated. Add 500 lb. / 227 kg for crating.

60"h x 33"w x 206" l. 152cm x 84cm x 523cm.

12 kVA, 60 amps

220V - 240V, Single Phase, 50/60 Hz.

100 psi min. - 150 psi Max.

Ambient temperatures ranging from 20c - 25c.

30%- 80%.

1 yr. warranty on all parts including print heads.

Contact your Local Distributor Machine includes, Technical training and setup, Choice of RIP, spare parts kit, Cleaning Station and Roll Lifter. F.O.B. Ontario, Canada.



Spectra High Performance Piezoelectric Jetting Assembly, quantity 18.

300 dots per inch, 6 color. Prints high quality at 600 dpi 6 color (apparent)

Roll substrate Max size: 5.0 meter/ 16' wide.

Reinforced Vinyl, Pressure Sensitive Vinyl, Canvas, Fabrics, Mesh and Paper.

Choice of Onyx PosterShop, Wasatch SoftRip, ColorGate, ErgoSoft on PC, And Caldera on the Mac.

EPS. Tiff. RGB. PostScript Level 3 etc..

1-3 years depending on location, Without a clear protective top coating. Using SWC top coat, print life will double.

> 6 Color 600dpi

Best Mode 500sf/hr Production Mode 750sf/hr User definable #passes vs % density

11,000 lbs/ 4545 kgs uncrated. Add 2500 lb. /1136 kg for crating.

72"h x 51"w x 290" l. 182cm x 130cm x 736cm.

25 kVA, 100amps.

220V - 240V, Single Phase, 50/60 Hz.

100 psi min. - 150 psi Max.

Ambient temperatures ranging from 20c - 25c.

30%-80%.

1 vr. warranty on all parts including print heads.

Contact your Local Distributor Machine includes,
Technical training and setup,
Choice of RIP, spare parts kit,
Cleaning Station and Roll Lifter.
F.O.B. Ontario, Canada.





Spectra High Performance Piezoelectric Jetting Assembly, quantity 24.

300 dots per inch, 4 / 6 / 12 color combo. Prints high quality at 1200 dpi 12 color (apparent).

Rigid Material, Max size: 3.048 meter/120 inches By 1.52 meter/60 inches.

Reinforced Vinyl, Pressure Sensitive Vinyl, Canvas, Fabrics, Foam Board, Corrugated Board, Rigid Plastics, Metal Sheet and Paper.

Choice of Onyx PosterShop, Wasatch SoftRip, ColorGate, ErgoSoft on PC, And Caldera on the Mac.

EPS, Tiff, RGB, PostScript Level 3 etc..

1-3 years depending on location, Without a clear protective top coating. Using SWC top coat, print life will double.

	4color 300dpi	600dpi	12color 1200d
Best Mode Sf/Hr Production Mode Sf/Hr	680 860	480 680	240 340
User definable #passes vs % density			

8000 lbs/ 3636 kgs uncrated. Add 2500 lb. /1136 kg for crating.

60"h x 96"w x 245" l. 152cm x 242cm x 617cm.

25 kVA, 100amps.

220V - 240V, Single Phase, 50/60 Hz.

100 psi min. - 150 psi Max.

Ambient temperatures ranging from 20c - 25c.

30%-80%.

1 yr. warranty on all parts including print heads.

Contact your Local Distributor Machine includes, Technical training and setup, Cleaning Station, Choice of RIP, spare parts kit, F.O.B. Ontario, Canada.